



Product Bulletin

Better Chemistry. **Better Business.**

Lusterlume LE

Product Code: 2103005
Revised Date: 03/01/2006

Lusterlume LE

Lusterlume LE is a mildly alkaline, powdered product used for burnishing solid brass, brass plated work, copper and zinc die-castings. It may also be used in aluminum steel and stainless steel.

One of the chief advantages of **Lusterlume LE** is that it can be used for operations in which long burnishing times are required to achieve the desired results. A long burnishing operation presents a number of problems such as breakdown of the burnishing product, and the darkening or rusting of the steel media. **Lusterlume LE** has been formulated to overcome these problems, most effectively in hard water areas.

OPERATING PARAMETERS

Concentrations:	1/2 to 2 oz/gal.
Temperature:	room to 120F.
Equipment:	open or closed barrels - lined or unlined.
Media:	part on part, steel shot or any media presently in use.

CAUTION

Although **Lusterlume LE** is mildly alkaline, avoid skin, eye and oral contact. Wear protective clothing, goggles and gloves when handling **Lusterlume LE**. If exposed, flush thoroughly with clear, cold water. In case of injury, please contact a doctor.

WASTE DISPOSAL

Discharge to a disposal system. In order to be completely informed on the latest regulations for your area, please contact the local authorities.

WARRANTY

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.